Manitoba Transportation and Government Services Traffic Engineering

WORK ZONE TRAFFIC CONTROL MANUAL

ROADSIDE WORK AND SHOULDER WORK

THIS LAYOUT APPLIES TO: SHORT DURATION WORK

REFER TO POLICY 900-E-2

RIGHT SHOULDER WORK

		S(km/h)	A(m)	L(m)	B(m)	D(m)
	[., ·.;]	50 60	50 50	60	35 45	15 15
			<u>50</u> 	90 120	<u>45</u> 50	15 15
		80	100	175	55	15
	•	90	100	200	65	20
		100	150	250	70	20
		WHERE:				
	.: :::	S = SPEED				
		A = SPACII L = LENGT			SNS	
		B = LENGT			NAL BUFI	FER SPAC
		D = SPACI				
	37.					
		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				\neg
		- Ö-				
		_		•••		
		OI 360° BEACON	R FI	LASHING	ARROW	
		AND		BOAF		
	4-	WAY FLASHERS	NOTE 'NO	E: NON-DI ARROW N	RECTIONA NODE ONI	AL _Y
	A					
		•				
	1					
		-				
	↑					

DATE OF ISSUE: 1997-12; REVISED: 2002-02

PATH: TESIGNS/Te-020.dgn

APPROVED:

TMP-3