



## **PLEASE NOTE**

This document, prepared by the [Legislative Counsel Office](#), is an office consolidation of this regulation, current to February 1, 2004. It is intended for information and reference purposes only.

This document is *not* the official version of these regulations. The regulations and the amendments printed in the [Royal Gazette](#) should be consulted to determine the authoritative text of these regulations.

For more information concerning the history of these regulations, please see the [Table of Regulations](#).

If you find any errors or omissions in this consolidation, please notify the Legislative Counsel Office at (902) 368-4291 or by email to [pmporter@gov.pe.ca](mailto:pmporter@gov.pe.ca).

## CHAPTER H-5

### HIGHWAY TRAFFIC ACT

#### SLOW MOVING VEHICLE SIGNS REGULATIONS

Made by the Lieutenant Governor in Council under the *Highway Traffic Act* R.S.P.E.I. 1988, Cap. H-5

1. A slow moving vehicle sign is hereby prescribed to be exhibited on any slow moving vehicle or equipment or animal-drawn vehicle or any other machinery designed for use at speeds less than forty kilometres per hour, and shall

Signs to be exhibited by slow moving vehicles

- (a) consist of fluorescent yellow-orange, base down equilateral triangle with a dark reflective border, bonded to a durable rigid weatherproof base surface of aluminium or steel in accordance with shape, minimum dimensions and color arrangement shown in Figure 1; and
- (b) be capable of being entirely visible day and night under normal atmospheric conditions from all distances from the rear between 180 and 30m and when directly in front of the high beam headlamps of a motor vehicle; and
- (c) be rigidly mounted or affixed wherever practical at the centre of the mass to the rear of such vehicle at a distance of 1 - 2 m above the surface of the roadway in the position shown in Figure 1 attached;
- (d) conform to the standards set by the Canadian Standards Association number CSA D198-1967. (EC320/81)

**FIGURE 1**

1. Metric linear dimensions are in millimeters.
2. Unless otherwise specified, a tolerance of 1.5 applies to all dimensions.

