



National Vector Data - Identification Rules

Edition 1.0

2006-01-23

**Natural Resources Canada
Geomatics Canada
Centre for Topographic Information
2144, King Street West, Suite 010
Sherbrooke (Quebec) Canada
J1J 2E8**

Telephone: 1-800-661-2638 (Canada and USA)
Fax: (819) 564-5698
E-mail: geobase@nrcan.gc.ca
URL: <http://www.geobase.ca>

Copyright Notice

© Her Majesty the Queen in Rights of Canada, Department of Natural Resources.
All rights reserved.

GeoBase®

REVISION HISTORY

Date	Version	Description
January – 2006	1.0	Original version

FUTURE WORK

Key-word	Description

TABLE OF CONTENTS

1 OVERVIEW..... 1

2 IDENTIFICATION STANDARD..... 1

3 NVD IDENTIFICATION STANDARD 2

4 NID VALUES 2

5 REFERENCES 3

ABBREVIATIONS

GUID	Globally Unique Identifiers
ID	Identifier
IEEE	Institute of Electrical and Electronics Engineers
NID	National Identifier
NRCan	Natural Resources Canada
NRNC1	National Road Network, Canada, Level 1
NSDI	National Spatial Data Infrastructure – USA
NVD	National Vector Data
UUID	Universal Unique Identifiers

TERMS AND DEFINITIONS

National Vector Data

Several layers of vector data, referred to as National Vector Data (NVD), will share the same specification. The Road Network (NRNC1) and Water Network are examples of NVD.

1 Overview

The objective is to update the NVD product on a regular basis as soon as mechanisms have been established between NVD's partners. One of the mechanisms is establishing change management principles. Two basic concepts are needed: identification rules and definition / classification of change.

On the Identification side, objects that depict real-world phenomena vary over time, either by their descriptive business case use or by the precision of the instruments and methods involved in their initial acquisition. One or more representation of the same phenomena may therefore exist. To illustrate, as part of this initiative, the goal is to build and maintain a **single** representation. Identifiers play a fundamental role in ensuring the proper exchange and circulation of the Objects modified at the source and already provided to users. The implementation of a standard for the permanent identification of a phenomenon and its application are to achieve two primary objectives:

- Facilitate the management and distribution of object changes in an incremental manner;
- Facilitate the conflation process, if necessary.

Every occurrence of NVD basic features must be uniquely identified: Each geometric object (such as in the NRNC1: *Road Element*, *Ferry Connection*, and *Junction*) as well as each event (in the LRS model) that describes specific characteristics of the linear network must also be uniquely identified.

2 Identification standard

The Identifiers must be permanently assigned. In order to ensure their stability, the assigned IDs must be insignificant (inconsequential) in their expression [1]. In other words, the IDs must not contain any information relative to the data. Past experience has demonstrated that encapsulating information within the ID can cause ID modification without any real change in the data having occurred.

Several standards have dealt with the Road Network. Most of them point to the importance of using Identifiers without ever specifying the manner, format, or method of application. These documents GDF [2], GIS-T (GIS in transportation data standards) [3] and CEN TC 278 [4] have no specifications related to Identifiers. National Spatial Data Infrastructure – USA (NSDI) Framework Transportation Identification Standard was the only document that clearly defined and described an Identifier code [5]. Within the ISO TC 211/SC: Geographic Information Standard - Encoding [6] we found a UUID definition that fit exactly our view:

“An application domain defines a universe and an identification scheme called universal unique identifiers (UUIDs). A UUID is assigned to an object when it is created and is stable over the object's entire life span. The UUID of a deleted object cannot be used again. UUIDs are required for long-term distributed data management and for implementing update mechanisms. These identifiers are also called persistent identifiers. A special name server may be used to resolve persistent identifiers. The identifiers are unique within a well-defined limited universe defined by an application domain.”

The ISO definition will be used for the “Identifier”. A generation mechanism is presented in the following section.

3 NVD Identification Standard

ID uniqueness is one of the fundamental characteristics that must be maintained. Two techniques for making IDs unique were studied.

- The first consists in mandating a firm to generate and manage ID ranges depending on data producers.
- The second consists in using a unique ID generation algorithm¹ that could be used by data producers with no particular management of range and domain.

The **second** method was selected. A UUID is an identifier that is unique across both space and time, with respect to the space of all UUIDs. UUID generation does not require a registration authority for each single identifier. Instead, it requires a unique value over space for each UUID generator. This spatially unique value is specified as an IEEE 802 address, which is usually already applied to network-connected systems. This 48-bit address can be assigned based on an address block obtained through the IEEE registration authority. This UUID specification assumes the availability of an IEEE 802 address.

The UUID consists of a 16-byte record and must not contain padding between fields. The total size is 128 bits. For use in human-readable text, a UUID string representation (32 characters) is specified as a sequence of fields. The following string is a UUID example:

- 378a3917e824422cb25f268b8295da51

For more information: http://www.opengroup.org/onlinepubs/9629399/apdx.htm#tagcjh_20

The assignation and persistence rules of the UUID are explained at the “*National Vector Data – Change Management*”² document.

4 NID Values

The algorithm described in the previous section provides flexibility while working with several partners. This well-known algorithm could be used by any data users to modify the data and add a new NID. **NIDs should only be generated by authorized organizations**. Specific care must be given to NIDs. These NIDs will eventually allow data synchronization between organizations. Data users must ensure that they make **no alterations whatsoever to these NIDs value**. Modifications would render NIDs useless for data synchronization.

¹ Readers who wish to use a standards-body definition of UUIDs/GUIDs should refer to: ISO/IEC 11578:1996 Information technology -- Open Systems Interconnection -- Remote Procedure Call <http://www.iso.ch/cate/d2229.html> or DCE 1.1: Remote Procedure Call Open Group Technical Standard Document Number C706, August 1997, 737 pages. (Supercedes C309 DCE: Remote Procedure Call 8/94, which was the basis for the ISO specification) <http://www.opengroup.org/publications/catalog/c706.htm>

² This document can be found at: <http://www.geobase.ca/geobase/en/data/nrnc1.html>

5 References

- 1 Bédard Y, Larrivé S et Proulx M-J. “*Travaux de modélisation pour la mise en place de la base de données géospatiale*“ *ISIS*, Laval University, March 2000
- 2 ISO Technical Committee 204, Working group 3, “*ISO/TR 14825 GDF – Geographic Data Files – Version 4.0*,” ISO/TC 204 N629, October 12, 2000
- 3 Dueker, Kenneth J. and Butler, J. Allison, “*GIS-T Enterprise Data Model with Suggested Implementation Choices*“,Center for Urban Studies School of Urban and Public Affairs Portland State University, October 1, 1997
- 4 <http://www.nen.nl/cen278>
- 5 National Spatial Data Infrastructure, “*NSDI FRAMEWORK TRANSPORTATION IDENTIFICATION STANDARD -- Public Review Draft*,” FGDC-STD-999.1-2000, Ground Transportation Subcommittee Federal Geographic Data Committee, December, 2000
- 6 ISO Technical Committee 211, Working Group 4, “*Geographic Information – Encoding*,” ISO/CD 19118.3, June 15, 2001